

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 027 832 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
16.08.2000 Bulletin 2000/33

(51) Int. Cl.⁷: **A23G 9/04**, A23G 9/12,
A23G 9/22

(21) Application number: **00200438.0**

(22) Date of filing: **10.02.2000**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Bravo, Genesio**
36041 Alte Di Montecchio Maggiore (IT)

(74) Representative:
Martegani, Franco
Patent Attorney,
Via Carlo Alberto, 41
20052 Monza (Milano) (IT)

(30) Priority: 11.02.1999 IT MI990261


(71) Applicant: **BRAVO S.p.A.**
I-36100 Vicenza (IT)

(54) **Process for the whipping of blended foodstuffs**

(57) The invention refers to a process for the whipping of blended foodstuffs, where a fluid blend is introduced into a whipping vessel equipped with cooling and mixing devices to process it into a pasty or creamy finished product. According to this invention, in the transitional phase from said fluid to a pasty state the blend is processed through a sequence of phases in which the mentioned blender rotates at different speeds. This achieves a product of superior quality.

Fig.5

Temperature vs. whipping velocity



EP 1 027 832 A1

Description

[0001] This invention refers to an enhanced process for the whipping of blended foodstuffs, in particular for the production of a so-called "handicrafted" ice cream. As the experts in the trade know very well, the "handicrafted" ice cream is mostly produced by two systems.

[0002] A first system comprises the following three phases:

1) Pasteurizing the basic blend by heating it up to +85°C and quick-cooling it down to a temperature of about +4°C, so as to eliminate the bacterial flora;

2) A curing process of the pasteurized blend at 4°C for an adequate period of time, for instance 12 hours;

3) Whipping of the cured blend while cooling it, until producing an ice cream of a structural consistency suitable for extracting it from the whipping unit, at temperatures, depending on the occasion, generally ranging from -8°C to -11°C.

[0003] In the trade, this system is commonly known as a "classic" or "traditional" method.

[0004] A second system known in the trade as a "tritych" method, does not consider the process of curing of the blend: in other words, the blend heated up to +85°C, is immediately cooled and contemporaneously whipped. Such a process can for example be carried out by using the machines described in the patents IT-996.102, IT-1.055.984, and EP-A-423.898, whose teachings may be considered as being part of this application.

[0005] In both systems briefly mentioned above, the whipping of the blend was carried out inside a cooled whipping cylinder, whose blender was rotated at constant speed throughout the entire whipping phase.

[0006] The blender was eventually accelerated merely to allow a quicker and easier extraction of the already whipped icecream from the cylinder, ready for consumption and/or storage.

[0007] The use of the above production systems allowed obtaining a "handicrafted" ice cream of excellent quality, exhibiting the desired organoleptic as well as structural properties.

[0008] It was however surprisingly discovered that while processing the blend in a whipping stage by rotating the whipping unit at various speeds (no longer at a constant single speed as in the known art), an ice cream of further improved overall properties from both an organoleptic and structural viewpoint was obtained while simultaneously reducing the whipping time during the various whipping stages, with all the ensuing advantages even from an energy viewpoint, which is assuming an ever greater importance in every trade.

[0009] The new and original feature of the invention lies therefore in obtaining a blended foodstuff by rotating the whipping blender at various speeds during the various whipping phases.

[0010] More precisely, the invention is based on a procedure for the whipping of blended foodstuffs - in particular for the production of "handicrafted" ice creams - where a blend in a liquid state is introduced into a whipping unit equipped with cooling devices for the blend, and a blender is capable of taking it to a pasty and/or creamy finished product condition, characterized in that the said blend is processed, in a transitional period from the said fluid to a pasty state, according to a sequence of phases in which the said blender rotates at different speeds.

[0011] The process of the invention is defined in the principal claim, and in its subordinate claims attached.

[0012] The process of the invention may be carried out by utilizing a whipping machine equipped with multiple rotating speed devices, appropriately set up to achieve the purpose.

[0013] In a preferential yet not essential way, the process of the invention may be carried out to advantage while using a blender driven by an alternate current motor, by a frequency "inverter" whose purpose is to change the blender's rotating speed, whenever desired and in an appropriately programmed manner.

[0014] For example, in order to execute the process of the invention, the entire whipping cycle may be carried out by controlling the current absorbed by the blender motor and regulating the rotating speed of the blender based on the same.

[0015] The regulating of the blender speed can, as mentioned above, be carried out by a motor feeding device commonly known as an "inverter".

[0016] Such a device varies the frequency of the sinusoidal feeding wave, and therefore of the whipping blender.

[0017] Utilizing for instance the "tritych" method, according to one possible embodiment of the process of this invention, the blend is poured into the whipping cylinder at a temperature of 85°C, and the initial blender speed is set for instance at 90 Hz (350 rpm). This first whipping phase, where the blender rotates at a speed of for example 350 rpm (90 Hz), may for example last for five minutes,

[0018] During this first blending phase, the absorption of current on the part of the motor is small because the blend, while cooling off at a very quick rate, is always in a liquid condition.

[0019] After 5 minutes of whipping, in a second phase the blender's rotating speed is for example lowered to 55 Hz (210 rpm), and remains at this value until the current absorption of the motor falls below a certain limit (LIM1).

[0020] When the current absorption of the motor exceeds other limits (LIM2 and LIM3) because the structure of the

blend turns ever more consistent, the blender's rotating speed is further reduced to 40 Hz (164 rpm) and 32 Hz (140 rpm).

[0021] At this point the whipping of the blend is complete and yields a pasty and/or creamy product of the desired consistency, which can be extracted from the whipping cylinder, eventually even while accelerating the blender's rotating speed.

[0022] The block diagram of Figure 1 outlines the phases of the described process in a simplified form.

[0023] The adoption of a whipping cycle as described above achieves, in addition to optimizing the performance of the machine used (for example, of a machine known in the market under the Triptych (TRITTICO) registered trademark, a finished product of superior quality.

[0024] The higher speed in the initial phase, when the blend is still in a liquid condition, in fact favors the homogenization and blending of the components of the same, as well as the inclusion or incorporation of air in the blend itself.

[0025] The subsequently reduced speeds, above all that in the final processing stage, improve the thermodynamic characteristics of the machine used, while favoring the exchange of heat with the walls of the whipping cylinder.

[0026] This allows attaining lower temperatures in less time.

[0027] The graph illustrated in Figure 2 of the drawings, offered for exemplifying and non-limiting purposes, illustrates the temperature and the time periods (expressed in seconds x 2), referred to an exemplifying quantity of a type of blend in the various phases of an example of embodiment of the process according to the invention.

[0028] The tests utilized a machine known in the market as "Executive Triptych 183" ("TRITTICO 183 EXECUTIVE").

[0029] The basic blend used consisted of: 2.5 liters of a blend with a 39% fat content, 975 grams of CREMIZIA ("registered trademark of the company Nuova Tradizione S.r.l.") in 1,525 grams of water.

[0030] An examination of the graph of Figure 2 allowed verifying the run of the temperatures during the whipping process according to the invention.

[0031] As can be clearly seen from the graph of Figure 2, the sample no. 274 (corresponding to a whipping time of 9 minutes) attains a temperature of -10°C.

[0032] The graph of Figure 3 compares the "TRITTICO" traditional method (utilizing a constant blender rotating speed) with the process according to the invention.

[0033] To ensure a parity of judgement, the tests were run on the same machine and with the same blend mentioned above.

[0034] In the first test the blend was processed at a constant speed according to the traditional TRITTICO method, while in the second test the whipping of the blend was run by varying the blender's rotating speed.

[0035] A temperature target of -10°C was set purely for the purposes of attaining a temperature of -10°C.

[0036] While operating in accordance with the invention (Line 2) at various blender rotating speeds, a temperature of -10°C was attained after 8 minutes and 40 seconds (260 samples x 2 = 520 seconds), whereas while operating under the traditional (constant speed) "TRITTICO" system, after a time of 13 minutes and 20 seconds the temperature of the whipped product had reached only -9.62°C.

[0037] The graphs of the Figures 4, 5 describe the whipping speeds in relation to two different examples of practical embodiment of the process according to the invention, where L1 indicates the whipping speed, and L2 the temperatures and cycling times of the whipping process.

[0038] The graph of Figure 6 offers a comparison between the "traditional" or "classic" whipping cycle, where the blend is introduced into the blender after curing at a temperature around +4°C, carried out at constant speed, and the process according to the invention carried out at variable speed. M1 is the classic method, M2 the method according to the invention.

[0039] In order to implement the process, the ingredients are added to the machine as usual, meaning by premixing the powders with each other and adding them to the liquid, for example to the milk, which has been previously brought up to a temperature of about 30°C. In the "TRITTICO" system, such a blend is heated up to 85°C and after reaching this temperature fed directly to the blender, so as to be directly subjected to the whipping process.

[0040] The tables given below outline the temperature data, the time periods, rotating speeds and overruns (air incorporations) in various tests run.

[0041] The tables 1, 2 and 3 refer to the process of the invention, while the Table 4 refers to the "TRITTICO" method.

1)	Hertz	Speed, rpm	Temperature, °C	Time, min.	Overrun, %
	80	320	-4	5	

(continued)

1)	Hert z	Speed, rpm	Temperature, °C	Time, min.	Overrun, %
	50	200	-8	8	
	40	164	- 10	8.5	28
2)	90	350	-5	5	
	60	240	- 7	6	
	40	164	- 10	7.5	33
3)	80	320	-4.5	5	
	60	240	- 8	7.5	
	40	164	- 10	8.5	30
4)	50	200	- 3.5	5	25
	50	200	-10	9	

[0042] Based on the tests run above, it is obvious that as the initial speed increases, the whipping time (at -10°C) decreases, the overrun (incorporation of air into the blend) increases, and the thermal stability of the product improves, or in other words that the measured dripping point under the traditional method is 13 minutes, while that under the method according to the invention (Test no. 2) is 15 minutes.

[0043] The scope of protection of the invention is defined by the following claims.

Claims

1. A process for the whipping of blended foodstuffs, in which a blend in a fluid state is introduced into a whipping unit equipped with devices to cool the blend, and a blender operating to bring it to the pasty or creamy condition of a finished product, characterized in that said blend is processed, during the transition from said fluid to pasty conditions, in accordance with a sequence of phases, during each of which said blender rotates at a different speed.
2. A process according to claim 1, characterized in that the blender's rotating speeds are decreasing from a higher initial speed at the time of introducing the blend into the whipping unit, to a lower final speed at the end of the whipping cycle.
3. A process according to claim 2, characterized in that short peaks of speed increases are provided between one decreasing speed and the other.
4. A process according to claim 1, characterized in that at the end of the whipping cycle the blender's rotating speed is accelerated to favor the extraction of the finished product.
5. A process according to claim 1, characterized in that it comprises four phases in which the blender's rotating speed is 90 Hz (350 rpm), 55 Hz (210 rpm), 40 Hz (164 rpm) and 32 Hz (140 rpm), respectively.
6. A process according to claim 1, characterized in that it comprises three phases in which the blender's rotating speed is 80 Hz (320 rpm), 50 Hz (200 rpm) and 40 Hz (164 rpm), respectively.
7. A process according to claim 1, characterized in that it comprises three phases in which the blender's rotating speed is 90 Hz (350 rpm), 60 Hz (240 rpm) and 40 Hz (164 rpm), respectively.
8. A process according to claim 1, characterized in that it comprises three phases in which the blender's rotating speed is 80 Hz (320 rpm), 60 Hz (240 rpm) and 40 Hz (164 rpm), respectively.
9. A whipping unit for executing the process according to the foregoing claims, equipped with a blender fitted with a multiple speed motor.
10. A whipping unit according to claim 9, characterized in that said motor is an alternate current motor equipped with a frequency "inverter".

- 11.** A whipping unit according to claim 10, characterized in that the entire whipping cycle is executed by controlling the current absorbed by the blender motor, while adjusting the rotating speed of the blender based on the same.

5

10

15

20

25

30

35

40

45

50

55


Fig.1

Fig.2

Whipping according to the invention




Fig.3

Comparison between a classic
and variable speed whipping




Fig.4

Temperature vs. whipping speed





Fig.5

Temperature vs. whipping velocity



Comparison between the "classic" method
and the method according to the invention




Fig.6



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 20 0438

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 091 825 A (THORN EMI) 19 October 1983 (1983-10-19) * page 5, line 6 - line 17 * * page 4, line 19 - line 33 *	1,4,9,10	A23G9/04 A23G9/12 A23G9/22
D,X	EP 0 423 898 A (BRAVO S.P.A.) 24 April 1991 (1991-04-24) * column 12, line 36 - column 14, line 55 *	1,4,9	
A	US 4 913 555 A (MAEDA ET AL.) 3 April 1990 (1990-04-03) * column 10, line 52 - column 13, line 40; figures 11-14 *	1	
A	US 4 545 216 A (CAVALLI) 8 October 1985 (1985-10-08) * column 3, line 12 - line 53 *	1	
A	FR 2 357 192 A (B.M. DEI FRATELLI BRAVO, GENESIO, FRANCESCO E GIUSEPPE S.N.C.) 3 February 1978 (1978-02-03)		
D	& IT 1 055 984 A		
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			A23G
Place of search	Date of completion of the search	Examiner	
THE HAGUE	15 May 2000	Lepretre, F	
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1508 (03.02.98) (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 20 0438

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on. The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

15-05-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 91825 A	19-10-1983	AU 1343383 A	20-10-1983
		DK 161383 A	17-10-1983
		FI 831241 A	17-10-1983
		JP 58190415 A	07-11-1983
		NO 831348 A	17-10-1983
		ZA 8302590 A	28-03-1984
EP 423898 A	24-04-1991	IT 1236757 B	02-04-1993
		CN 1051485 A	22-05-1991
		JP 3198745 A	29-08-1991
		US 5170344 A	08-12-1992
US 4913555 A	03-04-1990	JP 1634599 C	20-01-1992
		JP 2012085 B	19-03-1990
		JP 63174628 A	19-07-1988
		JP 1062111 A	08-03-1989
		CA 1302102 A	02-06-1992
		GB 2200855 A, B	17-08-1988
		KR 9107166 B	19-09-1991
		US 4993840 A	19-02-1991
US 4545216 A	08-10-1985	AU 2326684 A	19-07-1984
		BE 898671 A	02-05-1984
		BR 6400034 U	13-08-1985
		CA 1220947 A	28-04-1987
		CH 657250 A	29-08-1986
		DE 3400572 A	19-07-1984
		FR 2539273 A	20-07-1984
		GB 2133999 A, B	08-08-1984
		GR 79501 A	30-10-1984
		IL 70668 A	30-01-1987
		NL 8400093 A	01-08-1984
		ZA 8400284 A	29-08-1984
FR 2357192 A	03-02-1978	IT 1055984 B	11-01-1982
		DE 2706594 A	25-08-1977

EPO FORM P0438

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.